



[www.solardirect.cz](http://www.solardirect.cz)

Purchase Manager: +420 737 600 300

Email: [purchase@solardirect.cz](mailto:purchase@solardirect.cz)

Logistic: [tomas.kende@solardirect.cz](mailto:tomas.kende@solardirect.cz)

Regional sales: [novak@solardirect.cz](mailto:novak@solardirect.cz)

[kadrnozka@solardirect.cz](mailto:kadrnozka@solardirect.cz)

# REMOTE MONITORING AROUND THE CLOCK

## SOLAX CLOUD MONITORING

### Feature

- Local & Remote monitoring, setting and upgrade of batch inverters
- Intelligent export control, DRM control, ripple control and etc. of batch inverters
- Support large-capacity data storage
- Support IEC104 protocol



DataHub1000

Product Name	DataHub
Model	DataHub1000
Power Adapter	100-240V 50/60HZ 1.5A AC input 12V 2A DC output
Wireless Module	Wi-Fi 2.4GHz
Ethernet	10/100M
Manage Device Quantity	60
Interface	RS485*4, CAN*1, NET*1
Dry Contactor	AI*2, DI*4, DO*4
Data Transfer Interval	5 mins
Expanded Storage Capacity	8G/16G TF card (Optional)
Dimensions	205*124*33 mm
Weight	440g
Degree of Protection	IP21
Operating Temperature Range	-20°C ~ +60°C

Global sales manager Pavel Prochazka

+420724680736 | [prochazka@solardirect.cz](mailto:prochazka@solardirect.cz)

KAS Audio s.r.o., Distributor for LEAPTON Energy in Czech Republic

2. Floor, Libušská 400/115 - 142 00 Prague 4, Czech Republic

## Pocket WiFi V3.0



### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Offline data storage and resuming
- Multiple antenna adaptations according to the situation

Product Name	Pocket WiFi
Model	Pocket WiFi V3.0
Power Supply	5V 260mA DC
Wireless Module	Wi-Fi 2.4GHz
Antenna Gain	3dBi
Data Transfer Interval	5 mins
Dimensions	95.5*45.7*28.5 mm
Weight	50g
Degree of Protection	IP65
Operating Temperature Range	-40°C ~ +85°C

Product Name	Pocket LAN
Model	Pocket LAN V3.0
Power Supply	5V 180mA DC
Ethernet	10/100M
Data Transfer Interval	5 mins
Dimensions	112*45.7*28.5 mm
Weight	75g
Degree of Protection	IP65
Operating Temperature Range	-25°C ~ +75°C

## Pocket LAN V3.0



### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Offline data storage and resuming

## Pocket 4G V3.0



### Feature

- Quick installation with "Plug & Play" function
- IP 65 dust prevention water proofing designs
- Stable data transmission and good reliability
- Offline data storage and resuming
- Multi-communication operator support

Product Name	Pocket 4G
Model	Pocket 4G V3.0
Power Supply	5V 500mA DC
SIM Card Size	Nano - 4FF 12.3*8.8 mm
Support Band	LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 GSM: 850/900/1800/1900MHz
Data Transfer Interval	5 mins
Dimensions	112*45.7*28.5 mm
Weight	135g
Degree of Protection	IP65
Operating Temperature Range	-35°C ~ +75°C