

NEW FROM SOLAX

# X1-HYBRID G4



## X1-Hybrid G4

3.0kW/3.7kW/5.0kW  
6.0kW/7.5kW

## Features

### High-efficient

- 150% PV oversized and 110% overload output
- Maximum 120% overload output
- Higher efficiency on charging and discharging, up to 97.0%
- Built-in shadow tracking function

### Economic

- Maximum 16A DC input current, support for high power solar panel
- Store the surplus energy from PV to battery
- Low start output voltage makes inverter longer working time
- Less energy loss on battery to inverter

### Intelligent

- Switchover time <10ms
- Quick configuration with U-disk
- Lithium & Lead-acid battery compatible
- CT compatible, loads respond within 0.3s
- Intelligent loads management(e.g., Heat pump)
- On & Off-grid parallel function, up to 15kW
- 5 work modes, 2 charging periods available
- VPP ready, ancillary service in power market

### Safe

- IP65 protection level
- Integrated SPD

[www.solardirect.cz](http://www.solardirect.cz)

Purchase Manager: +420 737 600 300

Email: [purchase@solardirect.cz](mailto:purchase@solardirect.cz)

Logistic: [tomas.kende@solardirect.cz](mailto:tomas.kende@solardirect.cz)

Regional sales: [novak@solardirect.cz](mailto:novak@solardirect.cz) | [kadrmozka@solardirect.cz](mailto:kadrmozka@solardirect.cz)

Global sales manager Pavel Prochazka

📞 +420724680736 | 📧 [prochazka@solardirect.cz](mailto:prochazka@solardirect.cz)

📍 2. Floor, Libušská 400/115 - 142 00 Prague 4, Czech Republic

# X1-HYBRID G4 (SINGLE-PHASE)

X1-HYBRID-3.0-D  
X1-HYBRID-3.0-M

X1-HYBRID-3.7-D  
X1-HYBRID-3.7-M

X1-HYBRID-5.0-D  
X1-HYBRID-5.0-M

X1-HYBRID-6.0-D  
X1-HYBRID-6.0-M

X1-HYBRID-7.5-D  
X1-HYBRID-7.5-M

## DC INPUT

Max. PV array input power [Wp]	4500	5500	7500	9000	10000
Max. PV input voltage [V]	600	600	600	600	600
Start output voltage [V]	90	90	90	90	90
Nominal input voltage [V]	360	360	360	360	360
MPP voltage range [V]	70~550	70~550	70~550	70~550	70~550
No. of MPP trackers/Strings per MPP tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)
Max. input current(input A/input B) [A]	16/16	16/16	16/16	16/16	16/16
Max. short circuit current(input A/input B) [A]	20/20	20/20	20/20	20/20	20/20

## AC INPUT & OUTPUT

Nominal AC output power [W]	3000	3680	5000	6000	7500
Max. AC output apparent power [VA]	3300	3680	5500	6600	7500
Max. AC output current [A]	14.4	16	23.9	28.6	32.6
Max. AC input apparent power [VA]	6300	7360	9200	9200	9200
Max. AC input current [A]	27.4	32	40	40	40
Nominal AC voltage [V]	230/240				
Nominal grid frequency [Hz]	50/60				
Displacement power factor	0.8 leading~0.8 lagging				
THDi (rated power) [%]	<2				

## BATTERY DATA

Battery type	Li-ion battery/Lead-Acid Battery(Under development)				
Battery voltage range [V]	80-480				
Max. continuous charge/discharge current [A]	30				

## EPS(OFF-GRID OR BACK-UP) OUTPUT (WITH BATTERY)

Nominal output power [W]	3000	3680	5000	6000	7500
Peak apparent power [VA]	3600, 1h	3680	6000, 1h	7200, 10min	7500
Max. continuous current [A]	13	16	21.7	26.1	32.6
Nominal voltage[V]; Frequency [Hz]	230; 50/60				
Switch time [ms]	<10				
Parallel operation	YES				

## SYSTEM DATA

Max. efficiency [%]	97.6				
Euro. efficiency [%]	97.0				
Battery charge/discharge efficiency [%]*1	97.0/97.0				
Standby consumption [W] @Night	<3				
Degree of protection	IP65				
Operating temperature range [°C]	-35~+60 (Derating above 45°C)				
Max. operation altitude [m]	<3000				
Relative humidity [%]	0~100				
Typical noise emission [dB]	<30	<30	<30	<30	<45
Storage temperature [°C]	-40~+65				
Dimensions(WxHxD) [mm]	482x417x181				
Net weight [kg]	24	24	24	24	25
Cooling concept	Nature cooling	Nature cooling	Nature cooling	Nature cooling	Smart cooling
Communication interfaces	CT/ Meter(optional)/ External control Rs485/ Pocket WiFi(Optional: Pocket Lan/4G)/ DRM/ USB Upgrade/ NTC				

## STANDARD

Safety	EN/IEC62109-1/-2				
EMC	EN61000-6-1/2/3/4;EN61000-3-2/3/11/12				
Certification	VDE4105 /G99 /G98 / AS4777 / EN50549/ CEI 0-21 /IEC61727/RD1699/NRS 097-2-1/PEA/MEA/VR2019				

\*1: PV to BAT Max. efficiency 97.0%, BAT to AC Max. efficiency 97.0%

V2.1. Information may be subject to modify without notice. 650.00009.00